Specifications

Delivered OS compatibility USB cable (1,8 mm) Windows 2000 Windows XP Windows Vista Windows 7 (32, 64 bit)

point or comma

Output decimal mark (HID) Max. no. of cascadable interface

Timer function Mitutoyo measuring instruments with RS232C ouput

3 via optional link cable interval 0-99s or 0-99 min **KA-Counter**

Protractor Series 950 EH, EF, EV-Counter DP1-VR

Linear Height LH-600 OM-Data 200 Litematic VL-50

Laser Scan Micrometer LSM QM-Height

MF-Microscope Series PJ A3000 Projector PJ H30 Projector **ID-H Indicator**

Optional accessories

No.	Description			
937179T	Footswitch			
011538	Interface Link cable (300 mm)			

Specifications

Mass 84 g

Timer interval

1s./±99h 59 min 59s (100h)

tolerance

Power supply AC-Adapator 10 V, 120mA or USB bus

power

Delivered

With:

- USB connection cable (0.8 m)
- AC adaptor
- Footswitch cable TTB1 (0.52 m)



Sample application with DMX Box



Sample application with USB Input Tool Direct

DMX-3-2 USB

Series 011

The DMX-3-2 USB is a USB interface for connecting 3 Digimatic output measurement devices and 2 devices with RS232C output (e.g. Mitutoyo QM-Data 200) to the USB interface of a computer. A selection of more than 70 measuring instruments with RS232C output (Mitutoyo as well as other brands) can be connected to this interface (list is available on request).

The Interface converts the different signals fro the connected measuring instruments into the same format: keyboard signal (HID) or virtual COM-Port MUX-10 or MUX-50 (VCP).





Rear panel

011552

No.	Data input	Data Output	Interface ca- ble connection	Foot switch connector	Data bits	Bau- drate	Stop bits	Parity
011552	3 x Digimatic 2 x RS232C	USB virtual COM-Port (VCP) USB keyboard sig- nal (HID)	USB	•	8	9600	1	none

Timerbox

Series 011

Time controlled data transfer of measuring results

- Timerbox to connect to the footswitch connector of a Mitutoyo interface to trigger data transfer based on a time interval.
- Software neutral for all applications.
- For all Mitutoyo Interfaces featuring 3.5 mm TRS Foot switch connector (Mono) like USB Input **Tool Direct**
- This Timerbox is working as a time-controlled Footswitch



Dimensions (W x D x H) mm 011540 55 x 58 x 31

