## **Digimatic Micrometer**

## Series 293

- A cost-effective model with simplified functionality for applications.
- Available with a ratchet stop or friction thimble for a constant measuring force.



Functions	Series 293
ORIGIN	•
Auto Power OFF after 20 min. non use	<b>(4)</b>
Low voltage alarm	•

## **Specifications**

Accuracy Refer to the list of specifications

(excluding quantizing error)
Digital step 0,001 mm or 0,001 mm/0.00005"
Scales Thimble and sleeve satin chrome

finish ø18 mm

Flatness 0,3 µm
Parallelism 2 µm

Measuring Carbide tipped, micro-lap finish

surfaces Measuring

Measuring ø 6,35 mm, 0,5 mm pitch spindle

Measuring force 5-10 N

Battery life approx. 1.2 years

Delivered Including box, key, 1 battery

Certificate of inspection

## Consumable spares

	•
No.	Description
938882	Battery SR44





293-821

Metric		With ratchet stop		
No.	Range	Accuracy µm	Mass g	
293-821	0-25 mm	±2 μm	275	

Inch/Metric		With ratchet stop	
No.	Range	Accuracy µm	Mass g
293-831	0-1"	±2 μm/0.0001"	275

nch/Metric		With friction thimble	
No.	Range	Accuracy µm	Mass g
293-832	0-1"	±2 µm/0.0001"	275





