

Thread Plug Gauges

Series 941

6H tolerance

- GO/NG thread plug gauges to test threaded holes for compliance with the 6H tolerance.
- High quality products, case hardened to provide high wear resistance.



| No. | D Ø mm | A mm | B mm | G mm |
|------------|--------------|------|------|-------|
| 941-402* | M 2 x 0,40 | 3.6 | 2 | 9.25 |
| 941-402-2* | M 2,2 x 0,45 | 3.6 | 2.25 | 9.25 |
| 941-402-5* | M 2,5 x 0,45 | 3.6 | 2.5 | 9.25 |
| 941-403* | M 3 x 0,5 | 4.5 | 3 | 9.25 |
| 941-404* | M 4 x 0,7 | 6.2 | 3.5 | 9.25 |
| 941-405* | M 5 x 0,8 | 6 | 4.5 | 9.25 |
| 941-406* | M 6 x 1 | 8 | 4.5 | 9.25 |
| 941-407* | M 7 x 1 | 8 | 5 | 9.25 |
| 941-408* | M 8 x 1,25 | 10 | 6 | 9.25 |
| 941-409* | M 9 x 1,25 | 10 | 6 | 9.25 |
| 941-410* | M 10 x 1,5 | 12 | 8 | 9.25 |
| 941-411* | M 11 x 1,5 | 12 | 8 | 11.55 |
| 941-412* | M 12 x 1,75 | 16 | 8 | 11.55 |
| 941-414* | M 14 x 2 | 16 | 10 | 11.55 |
| 941-416* | M 16 x 2 | 20 | 10 | 16.17 |
| 941-418* | M 18 x 2,5 | 20 | 12 | 16.17 |
| 941-420* | M 20 x 2,5 | 20 | 12 | 16.17 |
| 941-422* | M 22 x 2,5 | 20 | 12 | 20.8 |
| 941-424* | M 24 x 3 | 24 | 14 | 20.8 |
| 941-427* | M 27 x 3 | 24 | 15 | 24.8 |
| 941-430* | M 30 x 3,5 | 24 | 14 | 24.8 |
| 941-433* | M 33 x 3,5 | 32 | 17.5 | 24.8 |
| 941-436* | M 36 x 4 | 32 | 20 | 24.8 |
| 941-439* | M 39 x 4 | 32 | 20 | 24.8 |
| 941-442* | M 42 x 4,5 | | | |
| 941-445* | M 45 x 4,5 | | | |
| 941-448* | M 48 x 5 | | | |

Specifications

Accuracy

UNI5870