

PV-5110 Measuring Projector

Series 304 - Accessories/Dimensions

Model	PV-5110
No.	304-909D 304-909E
Remarks	304-909E UK only
XY stage travel range (mm)	200 x 100
Measurement method	Linear encoder
Quick-release mechanism	X and Y axes
XY stage table top size (mm)	380 x 250
XY stage effective area (mm)	266 x 170
Stage glass No.	382762
Swiveling function	±3°
Max stage loading	5 kg

Standard accessories

No.	Description
172-402	10X projection lens set including : 172-409 Objective 172-410 Condenser
512305	Halogen bulb (24V, 150W)
12AAF182	Digital counter stand
382762	Stage glass 280x180 mm
172-419	Surface illumination unit

Optional accessories

No.	Description
172-401	5X projection lens set including : 172-406 Objective 172-407 Condenser 932602 Adapter for objective
172-403	20X projection lens set including : 172-411 Objective 172-412 Condenser
172-404	50X projection lens set including : 172-413 Objective 172-414 Condenser
172-405	100X projection lens set including : 172-415 Objective 172-414 Condenser
172-116	Standard scale 50 mm
172-330	Standard scale (80 mm)
172-161	Reading scale 300 mm
172-329	Reading scale (600 mm)
172-160-2	Green filter
172-319	Canopy
510189	Protective hood
172-198	Rotary table 100 mm with fine adjustment
172-197	Swivel centre support
176-107	Holder with clamp
172-378	V-block with clamp (Max. workpiece ø25 mm)
011534	Cleaner for optics
174-173D	KA-Counter 2 Axis
264-146D	QM-Data 200 Arm mount type
12AAE672	Detector mounting plate for ø500 to ø600 mm

Optional accessories for Inch

No.	Description
172-117	Standard scale (2")
172-162	Reading scale (12")
174-173E	KA-Counter 2 axis UK only
264-146E	QM-Data 200 Arm mount type UK only



172-319

