



Interchangeable Jaw Dimensions

Unit: mm


Standard type




Inside point type




Scriber type




Surface plate type



Centreline type



Scriber for height gauges



Interchangeable Jaw Specifications

Code No.	Components	a	b	Price
Standard type				
07CZA056*	2 pcs.	28 mm	30 mm	£201.00
Inside point type				
07CZA058*	2 pcs.	25 mm	50 mm	£240.00
07CZA059*	2 pcs.	1"	2"	£240.00
Scriber type				
07CZA055*	2 pcs.	8 mm	30 mm	£201.00
07CZA061*	2 pcs.	.031"	1.2"	£201.00

* Individual components available, price on application.

Code No.	Components	a	b	Price
Surface plate type				
07CZA044	1 pc.	90 mm	28 mm	£168.00
Centreline type				
07CZA057*	2 pcs.	30 mm	30 mm	£247.00
07CZA060*	2 pcs.	1.2"	1.2"	£247.00
Scriber for height gauges				
07GZA000	1 pc.	—	—	£34.90

* Individual components available, price on application.

Interchangeable Jaw	Applicable calipers	Range	Accuracy when attached to the caliper
Standard type	552-191-10	0 - 450 mm (0 - 18")	±0.06 mm (±.0025")
	552-192-10	0 - 600 mm (0 - 24")	
	552-193-10	0 - 1000 mm (0 - 40")	±0.07 mm (±.0030")
	552-194-10	0 - 1500 mm (0 - 60")	±0.11 mm (±.0045")
	552-195-10	0 - 2000 mm (0 - 80")	±0.14 mm (±.0055")
Inside point type	552-191-10	Inside: 50 - 500 mm (2 - 20")	±0.09 mm (±.0035")
		Outside: 0 - 450 mm (0 - 18")	
	552-192-10	Inside: 50 - 650 mm (2 - 26")	
		Outside: 0 - 600 mm (0 - 24")	
	552-193-10	Inside: 50 - 1050 mm (2 - 42")	±0.10 mm (±.0040")
		Outside: 0 - 1000 mm (0 - 40")	
	552-194-10	Inside: 50 - 1550 mm (2 - 62")	±0.14 mm (±.0055")
		Outside: 0 - 1500 mm (0 - 60")	
	552-195-10	Inside: 50 - 2050 mm (2 - 82")	±0.17 mm (±.0070")
		Outside: 0 - 2000 mm (0 - 80")	
Centreline type	552-191-10	30 - 480 mm (1.2 - 19.2")	±0.08 mm (±.0030")
	552-192-10	30 - 630 mm (1.2 - 25.2")	
	552-193-10	30 - 1030 mm (1.2 - 41.2")	±0.09 mm (±.0035")
	552-194-10	30 - 1530 mm (1.2 - 61.2")	±0.13 mm (±.0055")
	552-195-10	30 - 2030 mm (1.2 - 81.2")	±0.16 mm (±.0065")
Scriber type	552-191-10	30 - 480 mm (1.2 - 19.2")	±0.10 mm (±.0040")
	552-192-10	30 - 630 mm (1.2 - 25.2")	
	552-193-10	30 - 1030 mm (1.2 - 41.2")	±0.11 mm (±.0045")
	552-194-10	30 - 1530 mm (1.2 - 61.2")	±0.15 mm (±.0060")
	552-195-10	30 - 2030 mm (1.2 - 81.2")	±0.18 mm (±.0070")
Surface plate type and scriber type for height gauges	552-191-10	0 - 450 mm (0 - 17.7")	±0.10 mm (±.0040")
	552-192-10	0 - 600 mm (0 - 23.7")	
	552-193-10	0 - 1000 mm (0 - 39.4")	±0.11 mm (±.0045")
	552-194-10	0 - 1500 mm (0 - 59.4")	±0.15 mm (±.0060")
	552-195-10	0 - 2000 mm (0 - 79.6")	±0.18 mm (±.0070")
Surface plate type and inside point type	552-191-10	Inside: 25 - 475 mm (1 - 19")	±0.12 mm (±.0050")
		Outside: 0 - 450 mm (1 - 18")	
	552-192-10	Inside: 25 - 625 mm (1 - 25")	
		Outside: 0 - 600 mm (1 - 24")	
	552-193-10	Inside: 25 - 1025 mm (1 - 41")	±0.13 mm (±.0055")
		Outside: 0 - 1000 mm (1 - 40")	
	552-194-10	Inside: 25 - 1525 mm (1 - 62")	±0.17 mm (±.0070")
		Outside: 0 - 1500 mm (1 - 60")	
	552-195-10	Inside: 25 - 2025 mm (1 - 81")	±0.20 mm (±.0080")
		Outside: 0 - 2000 mm (1 - 80")	
Surface plate type and centreline type	552-191-10	15 - 465 mm (0.6 - 18.6")	±0.11 mm (±.0045")
	552-192-10	15 - 615 mm (0.6 - 24.6")	
	552-193-10	15 - 1015 mm (0.6 - 40.6")	±0.12 mm (±.0050")
	552-194-10	15 - 1515 mm (0.6 - 60.6")	±0.16 mm (±.0065")
	552-195-10	15 - 2015 mm (0.6 - 80.6")	±0.19 mm (±.0075")